

# OUTDOOR LIGHTING

## FACADE

## LED PROJECTOR

### AURA Series



#### OPTICAL SPECS

<b>Light Source:</b>	Cree
<b>Efficacy :</b>	80Lm/w
<b>CCT:</b>	2700-6000K
<b>CRI:</b>	>80/ >90 (Upon Reqeust)
<b>Beam Angle:</b>	5°,8°,10°,15°,20°,30°,45°,60

#### MECHANICAL SPECS

<b>Housing Material:</b>	Die cast Aluminum
<b>Diffuser:</b>	Tempered Glass with PMMA Lens
<b>Ingress Protection:</b>	IP65
<b>Impact Resistance:</b>	IK07
<b>Finish:</b>	Aluminum

#### ELECTRICAL SPECS

<b>Power:</b>	6-9-18W
<b>Input Voltage:</b>	220V AC
<b>Power Frequency:</b>	50-60Hz
<b>Power Factor:</b>	>0.9

#### OTHER SPECS

<b>Life Span:</b>	50,000H(L80B10)
<b>Operating Temperature:</b>	-20 - +50C
<b>Led Spec:</b>	COB
<b>Dimming:</b>	Dali / 0-10v (Optional)



OFFICE BUILDING



SHOPPING MALL



HOSPITALITY



AIRPORT

## AVAILABLE MODELS :

Part No.	Power	Output Lumen	Color Temperature	Light Source	Driver	Dimensions
AU-06-00**	6w	380lm	2700-6000K	Cree	Built-in	D 95mm*103mm*133mm
AU-09-00**	9w	570Lm	2700-6000K	Cree	Built-in	D 95mm*103mm*133mm
AU-18-00**	18w	1140Lm	2700-6000K	Cree	Built-in	D 110mm*117mm*168mm