

INDOOR LIGHTING

Recessed

Downlights

COMO-R Series



5 YEARS GUARANTEE

OPTICAL SPECS

Light Source:	Cree/Philips
Lumen Efficacy:	100-120lm/w
CCT:	2700K-3000K, 4000K, 6000K
CRI:	>80(>90 on request)
Beam Angle:	12°, 24°, 36°, 60°

MECHANICAL SPECS

Housing Material:	Cast Aluminum
Diffuser:	Tempered Glass
Reflector:	White/Black
Ingress Protection:	IP20/IP44
Installation:	Ceiling Recessed
Finish:	White/Black

ELECTRICAL SPECS

Power:	7-9-12-18-30-40W
Input Voltage:	220-240V AC
Power Frequency:	50-60Hz
Power Factor:	>0.9

OTHER SPECS

Life Span:	50,000H(L80B10)
Operating Temperature:	-20 - +40
Led Driver Spec:	Philips/Tridonic
Led Spec:	COB
Dimming:	Triac/Dali / 0-10v(Optional)

APPLICATIONS:



OFFICE BUILDING



RESIDENTIAL



SHOPPING MALL



RETAIL



HOSPITALITY

AVAILABLE MODELS :

Part No.	Power	Output Lumen	Color Temperature	Cut Out	Dimensions
CR-07-00*	7W	700Lm	2700-3000-4000-6000K	D85mm	D 95mm
CR-09-00*	9W	900Lm	2700-3000-4000-6000K	D85mm	D 95mm
CR-12-00*	12W	1200Lm	2700-3000-4000-6000K	D85mm	D 95mm
CR-18-00*	18W	1800Lm	2700-3000-4000-6000K	D85mm	D 95mm
CR-30-00*	30W	3000Lm	2700-3000-4000-6000K	D115mm	D125mm
CR-40-00*	40W	4000Lm	2700-3000-4000-6000K	D140mm	D151mm

* 00 REFER TO THE COLOR TEMPERATURE
(WW : WARM WHITE || NW : NATURAL WHITE || CW : COOL WHITE)