

# **INDOOR LIGHTING**

Recessed

Downlights

**COMO-SQ Series** 









#### **OPTICAL SPECS**

Light Source:	Cree/Philips
Lumen Efficacy:	100-120lm/w
CCT:	2700K ,3000K ,4000K,6000K
CRI:	>80(>90 on request)
Beam Angle:	12°,24°,36°, 60°

#### **ELECTRICAL SPECS**

Power:	18-30-45W	
Input Voltage:	220-240V AC	
Power Frequency:	50-60Hz	
Power Factor:	>0.9	

## MECHANICAL SPECS

Housing Material:	Cast Aluminum	
Diffuser:	Tempered Glass	
Reflector:	White/Black	
Ingress Protection:	IP20/IP44	
Installation:	Ceiling Recessed	
Finish:	White/Black	

### OTHER SPECS

Life Span:	50,000H(L80B10)	
Operating Temperature:	-20 - +40	
Led Driver Spec:	Philips/Tridonic	
Led Spec:	COB	
Dimming:	Triac/aDali / 0-10v(Optional)	

# **APPLICATIONS:**



OFFICE BUILDING



RESIDENTIAL



SHOPPING MALL



RETAIL



HOSPITALITY

## **AVAILABLE MODELS:**

Part No.	Power	Output Lumen	Color Temperature	Cut Out	Dimensions
CSQ-18-00*	18W	1800Lm	2700-3000-4000-6000K	85mm	95mm
CSQ-30-00*	30W	3000Lm	2700-3000-4000-6000K	115mm	125mm
CSQ-40-00*	45W	4500Lm	2700-3000-4000-6000K	140mm	151mm