

INDOOR LIGHTING

Recessed

Downlights

EDGE Series



OPTICAL SPECS

Light Source:	Philips
Lumen Efficacy:	100-120lm/w
CCT:	2700K,3000K,4000K,6000K
CRI:	>80
Beam Angle:	60°

ELECTRICAL SPECS

Power:	12-18W
Input Voltage:	220-240V DC
Power Frequency:	50-60Hz
Power Factor:	>0.9

MECHANICAL SPECS

Housing Material:	Cast Aluminum
Diffuser:	Tempered Glass
Reflector:	Black/Matt
Ingress Protection:	IP20/IP44
Installation:	Ceiling Recessed
Finish:	White/Black

OTHER SPECS

Life Span:	50,000H(L80B10)
Operating Temperature:	-20 - +40
Led Driver Spec:	Philips/Tridonic
Led Spec:	SMD
Dimming:	Triac/Dali / 0-10v(Optional)

APPLICATIONS:



OFFICE BUILDING



RESIDENTIAL



SHOPPING MALL



RETAIL



HOSPITALITY

AVAILABLE MODELS :

Part No.	Power	Output Lumen	Temperature	Cut Out	Dimensions
ED-12-00*	12W	1200Lm	2700-3000-4000-6000K	68mm	75mm
ED-18-00*	18W	1800Lm	2700-3000-4000-6000K	85mm	95mm
EDSQ-12-00*	12W	1200Lm	2700-3000-4000-6000K	125mm	140mm