

INDOOR LIGHTING

Linear

Down light Series

FUSION



OPTICAL SPECS

Light Source:	Cree/Philips
Lumen Efficacy:	100-120lm/w
CCT:	2700K,3000K,4000, 6000K
CRI:	>80
Beam Angle:	24°, 36°, 60°

ELECTRICAL SPECS

Power:	2-4-6-10-20W
Input Voltage:	220-240V AC
Power Frequency:	50-60Hz
Power Factor:	>0.9

MECHANICAL SPECS

Housing Material:	Aluminum
Diffuser:	Tempered Glass
Reflector:	Black/Specular
Ingress Protection:	IP20
Installation:	Ceiling Recessed
Finish:	White/Black

OTHER SPECS

Life Span:	50,000H(L80B10)
Operating Temperature:	-20 - +40
Led Driver Spec:	Philips/Tridonic
Led Spec:	COB
Dimming:	Triac/Dali / 0-10v(Optional)

AVAILABLE MODELS :

Part No.	Power		Output Lumen	Color Temperature	Dimensions
FU-02-00*	2W		160Lm	2700-3000-4000	45*45mm
FU-04-00*	4W		320Lm	2700-3000-4000	73*45mm
FU-06-00*	6W		480Lm	2700-3000-4000	94*45mm
FU-10-00*	10W		800Lm	2700-3000-4000	146*45mm
FU-20-00*	20W		1600Lm	2700-3000-4000	280*45mm