

INDOOR LIGHTING

Recessed

Downlights

JUPY Series



OPTICAL SPECS

Light Source:	Cree/Bridgelux
Lumen Efficacy:	100-120lm/w
CCT:	2700K,3000K,4000K,6000K
CRI:	>80
Beam Angle:	24°, 36°, 60°

MECHANICAL SPECS

Housing Material:	Cast Aluminum
Diffuser:	Tempered Glass
Reflector:	Black/Matt
Ingress Protection:	IP20
Installation:	Ceiling Recessed
Finish:	White/Black

ELECTRICAL SPECS

Power:	10-15-20-30W
Input Voltage:	220-240V DC
Power Frequency:	50-60Hz
Power Factor:	>0.9

OTHER SPECS

Life Span:	50,000H(L80B10)
Operating Temperature:	-20 - +40
Led Driver Spec:	Philips/Tridonic
Led Spec:	COB
Dimming:	Triac/Dali / 0-10v(Optional)

APPLICATIONS:



AVAILABLE MODELS :

Part No.	Power	Lumen	Temperature	Cut out	Dimensions
JU-10-00*	10W	1000Lm	2700-3000-4000-6000K	D85mm	D105mm
JU-15-00*	15W	1500Lm	2700-3000-4000-6000K	D105mm	D130mm
JU-20-00*	20W	2000Lm	2700-3000-4000-6000K	D120mm	D140mm
JU-30-00*	30W	3000Lm	2700-3000-4000-6000K	D140mm	D165mm