

OUTDOOR LIGHTING

LANDSCAPE

SPIKE

KALOU Series



By simply installing these reflectors you can vary the light cone angle without having to change the luminaire.

The product without reflector has a spot optic. For more fl exible lighting, install different optical reflectors on the same luminaire.



S - Spot BA from 15" to 24°



M - Medum BA from 24° to 60°



F - Flood BA >60°





TECHNICAL DATA

Material:	Die-Cast Aluminum Housing		
Diffuser:	Clear Toughened Glass		
Mounting:	Inground Floor Mounted		
Reflector:	Vacuum Coating Reflector		

ELECTRICAL DATA

LED Chip:	Philips/Cree	
Input Voltage:	AC110v/240V/12VDC	
IP Rating:	IP65	
Lifetime:	50,000 h	

APPLICATIONS:



RESIDENTIAL



OFFICE BUILDING







AVAILABLE MODELS:

Code	Voltage	Power	Size	Lumen	Beam Angle
KA-03-00*	AC220V/DC12V	3W	66*131*239mm	240LM	15°/25°/38°/60°
KA-07-00*	AC220V/DC12V	7W	76*150*289mm	595LM	15°/25°/38°/60°
KA-15-00*	AC220V/DC12V	15W	130*108*405mm	1200LM	24°
KA-30-00*	AC220V/DC12V	30W	189*146*473mm	1200LM	24°
KA-40-00*	AC220V/DC12V	40W	189*146*473mm	3400LM	24°