

OUTDOOR LIGHTING


LANDSCAPE

SPIKE


LIGO Series




By simply installing these reflectors you can vary the light cone angle without having to change the luminaire. The product without reflector has a spot optic. For more flexible lighting, install different optical reflectors on the same luminaire.



S - Spot
BA from 15° to 24°




M - Medium
BA from 24° to 60°



F - Flood
BA >60°

- LED COB: ☐ CREE ☐ PHILIPS

- Color temperature:
Cool white 6500K
Neutral white 4000K
Warm white 3000K
R / G / B
Purple



TECHNICAL DATA

Material:	Aluminum Housing
Diffuser:	Clear Toughened Glass
Mounting:	Inground Floor Mounted
Reflector:	Vacuum Coating Reflector

ELECTRICAL DATA

LED Chip:	Philips/Cree
Input Voltage:	AC 220/240V
IP Rating:	IP65
Lifetime:	50,000 h
CRI:	90
Driver:	Built In

APPLICATIONS:



RESIDENTIAL



OFFICE BUILDING



SHOPPING MALL



LANDSCAPE



HOSPITALITY

AVAILABLE MODELS :

Code	Voltage	Power	Size	Lumen	Beam Angle
LI-06-00*	AC220V/DC12V	6W	60*115*105mm	500LM	15°/25°/38°/60°
LI-09-00*	AC220V/DC12V	9W	79*130*130mm	800LM	15°/25°/38°/60°
LI-12-00*	AC220V/DC12V	12W	102*140*156mm	900LM	15°/25°/38°/60°