

INDOOR LIGHTING

SURFACE

Down lights

MUTE Series







ELECTRICAL SPECS

Power:	10W/14W/20W/24W		
Input Voltage:	220-240V AC		
Light Source:	LED COB – CREE/LUMINUS		
CCT:	2700K,3000K ,4000K,6000K		
Beam Angle:	15°/24°/36°/45°		
CRI:	>80 (Available >90 Upon Request)		
IP Protection:	IP20		
Driver:	PHILIPS, OSRAM, TRIDONIC		

MECHANICAL SPECS

Housing Material:	Die Cast Aluminum		
Diffuser:	Tempered Glass		
Installation:	Surface Mounted		
Shape:	Circular		
Finish:	White/Black & Customized		

APPLICATIONS:











AVAILABLE MODELS :

Model Number	Power	Output	Color Temperature Lumen	Dimensions
MU-10-00*	10w	1000Lm	2700/3000/4000/6500K	D72mm*H110mm
MU-14-00*	14w	1400Lm	2700/3000/4000/6500K	D80mm*H120mm
MU-20-00*	20w	2000Lm	2700/3000/4000/6500K	D90mm*H132mm
MU-24-00*	24W	2400LM	2700/3000/4000/6500K	D100mm*H135mm

30