

OUTDOOR LIGHTING

FACADE

UPLIGHT

SEAL Series



OPTICAL SPECS

Light Source:	Cree
Efficacy:	80 Lm/w
CCT:	2700-6000K
CRI:	>80 / >90 (Upon Request)
Beam Angle:	5°, 8°, 10°, 15°, 20°, 30°, 45°, 60°

MECHANICAL SPECS

Housing Material:	Diecast Aluminum
Diffuser:	Tempered Glass
Ingress Protection:	IP67
Impact Resistance:	IK08
Finish:	Stainless Steel

ELECTRICAL SPECS

Power:	3-6W 9-12W
Input Voltage:	220 AC
Power Frequency:	50-60Hz
Power Factor:	>0.9

OTHER SPECS

Life Span:	50,000H(L80B10)
Operating Temperature:	-20 - +50C
Led Spec:	COB
Dimming:	Triac/Dali / 0-10v(Optional)

APPLICATIONS:



OFFICE BUILDING



SHOPPING MALL



HOSPITALITY



AIRPORT

AVAILABLE MODELS :

Part No.	Power	Output Lumen	Color Temperature	Light Source	Driver	Dimensions
SE-103-00	3W	240Lm	2700-6000K	Cree	Built-in	¢100mm*120mm
SE-106-00	6W	480Lm	2700-6000K	Cree	Built In	¢100mm*120mm
SE-109-00	9W	720Lm	2700-6000K	Cree	Built In	¢ 160*155mm
SE-112-00	12W	960Lm	2700-6000K	Cree	Built In	¢160*155mm