

INDOOR LIGHTING

RECESSED

Fixed Spotlight

SHUTTLE SERIES



OPTICAL SPECS

Light Source:	Cree/Philips
Lumen Efficacy:	100-120lm/w
CCT:	3000K, 4000K, 6000K
CRI:	>80
Beam Angle:	24°, 36°, 60°

ELECTRICAL SPECS

Power:	5-7-9-12-15W
Input Voltage:	220-240V AC
Power Frequency:	50-60Hz
Power Factor:	>0.5

MECHANICAL SPECS

Housing Material:	Aluminum
Diffuser:	Tempered Glass
Ingress Protection:	IP20
Installation:	Ceiling Recessed
Finish:	White/Black/Customized

OTHER SPECS

Life Span:	50,000H(L80B10)
Operating Temperature:	-20 - +40
Led Driver Spec:	Philips/Tridonic
Led Spec:	COB
Dimming:	Triac/Dali / 0-10v(Optional)

APPLICATIONS:



AVAILABLE MODELS :

Part No.	Power	Output Lumen	Color Temperature	Cut-Out	Dimensions
SH-05-00*	5W	500 lm	2700-3000-4000-6000K	75mm	90*65mm
SH-07-00*	7W	700 lm	2700-3000-4000-6000K	75mm	90*65mm
SH-09-00*	9W	900 lm	2700-3000-4000-6000K	95mm	110*75mm
SH-12-00*	12W	1200 lm	2700-3000-4000-6000K	95mm	110*75mm
SH-15-00*	15W	1500 lm	2700-3000-4000-6000K	120mm	138*95mm